

TRANCE ADVANCED PRO 29 2

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Metal/Black / Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
FORK	Fox 34 Performance Elite Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Performance Elite Live Valve, 185/50, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Shimano Deore XT BR-M6120, hydraulic, Shimano RT-56 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512-1, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit
WHEELS	
RIMS	Giant TRX 2 Carbon 29 WheelSystem
HUBS	Giant TRX 2 Carbon 29 WheelSystem
SPOKES	Giant TRX 2 Carbon 29 WheelSystem
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size

FEATURES

- Frame: Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
- Fork: Fox 34 Performance Elite Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
- Shifters: Shimano SLX SL-M7100, 1x12
- Crankset: Shimano MT512-1, 30t S:165mm, M:170mm, L:170mm, XL:170mm
- Colors: Metal/Black / Chrome

Recommended Retail Price: \$6,000

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (inch)	16.5	16.9	18.3	19.5
Seat Tube Angle	77.2° 78.0°	76.3° 77.0°	76.3° 77.0°	76.3° 77.0°
Top Tube Length (inch)	22.1 22	23.6 23.5	24.6 24.6	26.1 26
Head Tube Length (inch)	3.9	4.3	4.7	5.1
Head Tube Angle	65.4° 66.2°	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°
Fork Rake (inch)	1.7	1.7	1.7	1.7
Trail (inch)	5 4.7	5 4.7	5 4.7	5 4.7
Wheelbase (inch)	45.9 45.9	47 47	48.2 48.1	49.7 49.7
Chain Stay Length (inch)	17.3 17.2	17.3 17.2	17.3 17.2	17.3 17.2
Bottom Bracket Drop (inch)	1.8 1.4	1.8 1.4	1.8 1.4	1.8 1.4
Stack (inch)	24 23.8	24.4 24.1	24.7 24.5	25.1 24.8
Reach (inch)	16.6 16.9	17.6 17.9	18.6 18.9	20 20.3
Stand Over Height (inch)	28.7 29	28.5 28.8	29.4 29.7	29.6 29.9
Handlebar Width (inch)	30.7	30.7	30.7	30.7
Stem Length (inch)	1.6	1.6	2	2
Crank Length (inch)	6.5	6.7	6.7	6.7
Wheel Size	29"	29"	29"	29"

**All specifications and prices listed are subject to change without notice.*